



EN14351-1:2006 + A1:2010

Windowbuild

55 – 56 Lewis Road
Cardiff, CF24 5EP



Edition: Dec 2015

DoP Ref.: CW002

DECLARATION OF PERFORMANCE

Double-glazed Elite 70 PVCu Casement Sash Window

CW – Elite 70 PVCu Casement Window

Window intended use not on escape route.

Essential performance characteristics

ID	Characteristics	CW						
1	Resistance to wind load (EN 12210)	<i>npd</i>						
2	Watertightness (EN 12208)	<i>npd</i>						
3	Dangerous substances ¹	<i>None</i>						
4	Load-bearing capacity of safety device ^{2,3 & 4}	<i>350N</i>						
5	Acoustic performance (EN ISO 140-3)	<i>npd</i>						
6	Thermal transmittance ⁵ (EN ISO 10077-1)	<i>≤ 1.6 W/(m².K)</i>						
7	Radiation properties (EN 410)	<i>npd</i>						
8	Air permeability (EN 12207)	<i>npd</i>						

BSI 0086 performed type test and issued KM 27900. ¹From statement issued by British Plastics Federation. ²Report WIL 328855 issued by Exova Warringtonfire

³Report TR1209 issued by Winkhaus, ⁴ Report 191795 EXOVA Warrington APT 0621 ⁵By calculation using EN ISO 10077-1

Declaration of conformity: I, the undersigned hereby declare conformity with the above Directive(s) and Standard(s) as shown

Signature:

Print: Chris Belcher

Title: General Manager